(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property **Organization**

International Bureau



(43) International Publication Date 25 November 2004 (25.11.2004)

PCT

(10) International Publication Number WO 2004/102499 A1

(51) International Patent Classification⁷:

G08B 17/10

(21) International Application Number:

PCT/AU2004/000639

(22) International Filing Date:

14 May 2004 (14.05.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:


2003902318

14 May 2003 (14.05.2003) ΑU

(71) Applicant (for all designated States except US): VISION FIRE & SECURITY PTY LTD [AU/AU]; 495 Blackburn Road, Mount Waverley, Victoria 3149 (AU).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,



introduced at a predetermined point in time of the duration of the second signal; receiving said first and second transmitted signals; determining a point of diversion between corresponding characteristic waveform features of the first and second received signals comprising super positioning said first and second received signals such that said point of diversion corresponds to an arrival time of the introduced waveform feature modification at the receiver. In a preferred embodiment, the invention provides an accurate time of flight determination of ultrasonic signals in a flow sensor (24) adapted for a smoke detector system (10).

